Section 1 CCCS Community and Community

	ion 1 - GCCS Components and Comments	SITE NAME:	Cottonwood Hills RDF
	Control Device or Fuel Skid - describe:		
/	Control Device or Fuel Skid - describe: Gas Mover Equipment - describe: FIRE Monitoring/Recording Equipment - describe: Chart Records		
/	Monitoring/Recording Equipment - describe: Chart RECORDER		
	Comments: Blower & Autovalve FROZE in SubZERO TEMPS.		

Section 2 - All Events

Type of				Event Description	SOP	* Followed?
Event	Date/Time Start	Date/Time End	Duration (hours)	(use pull-down menu)	Yes	No**
Shutdown	1.6.14/0206		58.5		/	
Startup		1.8.14/1236	0.1		/	
Malfunction					Complete	Section 3 Below

^{*} Standard Operating Procedure (SOP) for Flare/Fuel Skid Startups (Manual & Automatic) and Shutdowns are provided in SSM Plan

Section 3 - Malfunction Events Only

		Check one of the following for each step:		
Step	Corrective Action Procedures for All Malfunctions	Procedure completed	Procedure Not Applicab	
1.	Determine if the malfunction is causing an unsafe operating condition (air entering landfill or piping, smoking, vibration, or other problem), which may harm people, the environment or the landfill gas control equipment. If conditions are unsafe, notify your supervisor and follow steps under No. 3			
2.	Determine if landfill gas being released to the atmosphere (can you smell landfill gas, or measure or detect uncombusted gas flow?). If landfill gas is being released, follow steps under No. 3			
3.	If unsafe operating condition exists, or landfill gas is being released to the atmosphere, stop (if possible) landfill gas flow by one or more of the following: a. Close nearest valve to source of emissions b. Place a temporary cap on piping c. Apply other device (i.e. duct tape) d. Shut down blower e. Turn off main power disconnect switch to blower f. Other (Describe): Note: If flare is shut down, follow shutdown SOP and record shutdown time in Section 1 (above)			
4.	Detemine if other personnel or resource (qualified technician, electrician, consultant or other) are needed for malfunction diagnosis. If other personnel or resources are not needed, go to No. 6			
5.	Contact qualified personnel or resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #5.a.			
6.	Start malfunction diagnosis.			
	Determine if other resources are needed to fix the malfunction (qualified technician, electrician, contractor, on-site resources, manufacturer's representative, or other). If other resources are not needed, go to No. 9		,	
8.	Contact other qualified resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #8.a.			
9.	Fix the malfunction.			
	Once the malfunction is fixed, re-start the system per SOP if it had been shut down, and record start-up times and dates on this form.			
	Record date that malfunction occurred, date that malfunction was repaired, and total time that system was out of service in boxes in Section 1 of this form.			
12.	Sign this form, copy it, and place it in the Start-up, Shutdown, Malfunction Report Form file.			
13	If the procedures listed above were not followed, contact the site engineer immediately.			

 $[\]ensuremath{^{**}\text{If SOP}}$ in SSM Plan was not followed, notify site engineer immediately.

Section 1 - GCCS Components and Comments Control Device or Fuel Skid - describe: Gas Mover Equipment - describe: Monitoring/Recording Equipment - describe: Comments: Row out of Nitrogen

Section 2 - All Events

Type of				Event Description	SOP	* Followed?
Event	Date/Time Start	Date/Time End	Duration (hours)	(use pull-down menu)	Yes	No**
Shutdown	1.17.14/1526		1.9		/	
Startup		1.17.14/1720	0.1		/	
Malfunction					Complete S	Section 3 Below

^{*} Standard Operating Procedure (SOP) for Flare/Fuel Skid Startups (Manual & Automatic) and Shutdowns are provided in SSM Plan

Section 3 - Malfunction Events Only

		Check one of the following for	each step:
Step	Corrective Action Procedures for All Malfunctions	Procedure completed	Procedure Not Applicable
1.	Determine if the malfunction is causing an unsafe operating condition (air entering landfill or piping, smoking, vibration, or other problem), which may harm people, the environment or the landfill gas control equipment. If conditions are unsafe, notify your supervisor and follow steps under No. 3		
2.	Determine if landfill gas being released to the atmosphere (can you smell landfill gas, or measure or detect uncombusted gas flow?). If landfill gas is being released, follow steps under No. 3		
3.	If unsafe operating condition exists, or landfill gas is being released to the atmosphere, stop (if possible) landfill gas flow by one or more of the following: a. Close nearest valve to source of emissions b. Place a temporary cap on piping c. Apply other device (i.e. duct tape) d. Shut down blower e. Turn off main power disconnect switch to blower f. Other (Describe): Note: If flare is shut down, follow shutdown SOP and record shutdown time in Section 1 (above)		
4.	Detemine if other personnel or resource (qualified technician, electrician, consultant or other) are needed for malfunction diagnosis. If other personnel or resources are not needed, go to No. 6		
5.	Contact qualified personnel or resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #5.a.		
6.	Start malfunction diagnosis.		×
7.	Determine if other resources are needed to fix the malfunction (qualified technician, electrician, contractor, on-site resources, manufacturer's representative, or other). If other resources are not needed, go to No. 9		
8.	Contact other qualified resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #8.a.		
9.	Fix the malfunction.		
	Once the malfunction is fixed, re-start the system per SOP if it had been shut down, and record start-up times and dates on this form.		
11.	Record date that malfunction occurred, date that malfunction was repaired, and total time that system was out of service in boxes in Section 1 of this form.		
12.	Sign this form, copy it, and place it in the Start-up, Shutdown, Malfunction Report Form file.		
13.	If the procedures listed above were not followed, contact the site engineer immediately.		

 $[\]ensuremath{^{**}}\xspace$ If SOP in SSM Plan was not followed, notify site engineer immediately.

Section 1 - GCCS Components and Comments

Control Device or Fuel Skid - describe:

Gas Mover Equipment - describe:

Monitoring/Recording Equipment - describe:

Comments:

Comments:

Comments:

Comments:

Section	2 -	AII	FVC	nte
SECTION	Z -	AII		

Type of				Event Description	SOP*	Followed?
Event	Date/Time Start	Date/Time End	Duration (hours)	(use pull-down menu)	Yes	No**
Shutdown	3.12.14/1414		6.2			
Startup		3-12-14/1428	0,1		/	-
Malfunction					Complete S	ection 3 Below

^{*} Standard Operating Procedure (SOP) for Flare/Fuel Skid Startups (Manual & Automatic) and Shutdowns are provided in SSM Plan

Section 3 - Malfunction Events Only

CA	Commedian Antina Bassa I	Check one of the following for	
Step	Corrective Action Procedures for All Malfunctions	Procedure completed	Procedure Not Applicable
1.	Determine if the malfunction is causing an unsafe operating condition (air entering landfill or piping, smoking, vibration, or other problem), which may harm people, the environment or the landfill gas control equipment. If conditions are unsafe, notify your supervisor and follow steps under No. 3		
2.	Determine if landfill gas being released to the atmosphere (can you smell landfill gas, or measure or detect uncombusted gas flow?). If landfill gas is being released, follow steps under No. 3		
3.	If unsafe operating condition exists, or landfill gas is being released to the atmosphere, stop (if possible) landfill gas flow by one or more of the following: a. Close nearest valve to source of emissions b. Place a temporary cap on piping c. Apply other device (i.e. duct tape) d. Shut down blower e. Turn off main power disconnect switch to blower f. Other (Describe): Note: If flare is shut down, follow shutdown SOP and record shutdown time in Section 1 (above)		
4.	Detemine if other personnel or resource (qualified technician, electrician, consultant or other) are needed for malfunction diagnosis. If other personnel or resources are not needed, go to No. 6		
5.	Contact qualified personnel or resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #5.a.		
6.	Start malfunction diagnosis.		
	Determine if other resources are needed to fix the malfunction (qualified technician, electrician, contractor, on-site resources, manufacturer's representative, or other). If other resources are not needed, go to No. 9		
8.	Contact other qualified resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #8.a.		
9.	Fix the malfunction.		
	Once the malfunction is fixed, re-start the system per SOP if it had been shut down, and record start-up times and dates on this form.		
	Record date that malfunction occurred, date that malfunction was repaired, and total time that system was out of service in boxes in Section 1 of this form.		
12.	Sign this form, copy it, and place it in the Start-up, Shutdown, Malfunction Report Form file.		
13.	f the procedures listed above were not followed, contact the site engineer immediately.		,

 $[\]ensuremath{^{**}}\xspace$ If SOP in SSM Plan was not followed, notify site engineer immediately.

Section 1 - GCCS Components and Comments Control Device or Fuel Skid - describe: Gas Mover Equipment - describe: Monitoring/Recording Equipment - describe: Comments: Washler - Autorestant

Section	2 - All	Events

Type of Event	Date/Time Start	Date Time Ford		Event Description		* Followed?
Everil		Date/Time End	Duration (hours)	(use pull-down menu)	Yes	No**
Shutdown	5.22.14/1054		0,4		/	
Startup		5.22.14/1120	0.1		/	
Malfunction					Complete	Section 3 Below

^{*} Standard Operating Procedure (SOP) for Flare/Fuel Skid Startups (Manual & Automatic) and Shutdowns are provided in SSM Plan

Section 3 - Malfunction Events Only

		Check one of the following for	each step:
Step	Corrective Action Procedures for All Malfunctions	Procedure completed	Procedure Not Applicat
1.	Determine if the malfunction is causing an unsafe operating condition (air entering landfill or piping, smoking, vibration, or other problem), which may harm people, the environment or the landfill gas control equipment. If conditions are unsafe, notify your supervisor and follow steps under No. 3		
2.	Determine if landfill gas being released to the atmosphere (can you smell landfill gas, or measure or detect uncombusted gas flow?). If landfill gas is being released, follow steps under No. 3		
3.	If unsafe operating condition exists, or landfill gas is being released to the atmosphere, stop (if possible) landfill gas flow by one or more of the following: a. Close nearest valve to source of emissions b. Place a temporary cap on piping c. Apply other device (i.e. duct tape) d. Shut down blower e. Turn off main power disconnect switch to blower f. Other (Describe): Note: If flare is shut down, follow shutdown SOP and record shutdown time in Section 1 (above)		
4.	Detemine if other personnel or resource (qualified technician, electrician, consultant or other) are needed for malfunction diagnosis. If other personnel or resources are not needed, go to No. 6		
5.	Contact qualified personnel or resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #5.a.		
6.	Start malfunction diagnosis.		2
7.	Determine if other resources are needed to fix the malfunction (qualified technician, electrician, contractor, on-site resources, manufacturer's representative, or other). If other resources are not needed, go to No. 9		
8.	Contact other qualified resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #8.a.		
9.	Fix the malfunction.		
10.	Once the malfunction is fixed, re-start the system per SOP if it had been shut down, and record start-up times and dates on this form.		
	Record date that malfunction occurred, date that malfunction was repaired, and total time that system was out of service in boxes in Section 1 of this form.		
12.	Sign this form, copy it, and place it in the Start-up, Shutdown, Malfunction Report Form file.		
13.	If the procedures listed above were not followed, contact the site engineer immediately.		

Signature: WWW.

 $[\]ensuremath{^{**}\text{If SOP}}$ in SSM Plan was not followed, notify site engineer immediately.

Section 1 - GCCS Components and Comments

Control Device or Fuel Skid - describe:

Gas Mover Equipment - describe:

Monitoring/Recording Equipment - describe:

Comments:

OHILLA POWER LOSS.

Type of					Event Description	SOP* Followed?	
Event	Date/T	ime Start	Date/Time End	Duration (hours)	(use pull-down menu)	Yes	No**
Shutdown	5.26.14	/1620		1.6		/	
Startup	/		5.26.14/1754	0.1		/	
Malfunction						Complete Section 3 Below	

^{*} Standard Operating Procedure (SOP) for Flare/Fuel Skid Startups (Manual & Automatic) and Shutdowns are provided in SSM Plan

Section 3 - Malfunction Events Only

		Check one of the following for	each step:
Step	Corrective Action Procedures for All Malfunctions	Procedure completed	Procedure Not Applicable
1.	Determine if the malfunction is causing an unsafe operating condition (air entering landfill or piping, smoking, vibration, or other problem), which may harm people, the environment or the landfill gas control equipment. If conditions are unsafe, notify your supervisor and follow steps under No. 3		
2.	Determine if landfill gas being released to the atmosphere (can you smell landfill gas, or measure or detect uncombusted gas flow?). If landfill gas is being released, follow steps under No. 3		
3.	If unsafe operating condition exists, or landfill gas is being released to the atmosphere, stop (if possible) landfill gas flow by one or more of the following: a. Close nearest valve to source of emissions b. Place a temporary cap on piping c. Apply other device (i.e. duct tape) d. Shut down blower e. Turn off main power disconnect switch to blower f. Other (Describe): Note: If flare is shut down, follow shutdown SOP and record shutdown time in Section 1 (above)		
4.	Detemine if other personnel or resource (qualified technician, electrician, consultant or other) are needed for malfunction diagnosis. If other personnel or resources are not needed, go to No. 6		
5.	Contact qualified personnel or resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #5.a.		
6.	Start malfunction diagnosis.		
7.	Determine if other resources are needed to fix the malfunction (qualified technician, electrician, contractor, on-site resources, manufacturer's representative, or other). If other resources are not needed, go to No. 9		-
8.	Contact other qualified resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #8.a.		
9.	Fix the malfunction.		
10.	Once the malfunction is fixed, re-start the system per SOP if it had been shut down, and record start-up times and dates on this form.		
	Record date that malfunction occurred, date that malfunction was repaired, and total time that system was out of service in boxes in Section 1 of this form.		
12.	Sign this form, copy it, and place it in the Start-up, Shutdown, Malfunction Report Form file.		
13.	If the procedures listed above were not followed, contact the site engineer immediately.		

^{**}If SOP in SSM Plan was not followed, notify site engineer immediately.

Section 1 - GCCS Components and Comments

Control Device or Fuel Skid - describe:

Gas Mover Equipment - describe:

Comments: Control Device or Fuel Skid - des

Section	2 -	EVA	nte

Type of				Event Description	SOP	* Followed?
Event	Date/Time Start	Date/Time End	Duration (hours)	(use pull-down menu)	Yes	No**
Shutdown	6.18.14/1040		1.1		/	
Startup		6.18.14/1146	0.1		/	
Malfunction					Complete Section 3 Below	

^{*} Standard Operating Procedure (SOP) for Flare/Fuel Skid Startups (Manual & Automatic) and Shutdowns are provided in SSM Plan

Section 3 - Malfunction Events Only

		Check one of the following for	each step:
Step	Corrective Action Procedures for All Malfunctions	Procedure completed	Procedure Not Applicable
1.	Determine if the malfunction is causing an unsafe operating condition (air entering landfill or piping, smoking, vibration, or other problem), which may harm people, the environment or the landfill gas control equipment. If conditions are unsafe, notify your supervisor and follow steps under No. 3		
2.	Determine if landfill gas being released to the atmosphere (can you smell landfill gas, or measure or detect uncombusted gas flow?). If landfill gas is being released, follow steps under No. 3		
3.	If unsafe operating condition exists, or landfill gas is being released to the atmosphere, stop (if possible) landfill gas flow by one or more of the following: a. Close nearest valve to source of emissions b. Place a temporary cap on piping c. Apply other device (i.e. duct tape) d. Shut down blower e. Turn off main power disconnect switch to blower f. Other (Describe): Note: If flare is shut down, follow shutdown SOP and record shutdown time in Section 1 (above)		
4.	Detemine if other personnel or resource (qualified technician, electrician, consultant or other) are needed for malfunction diagnosis. If other personnel or resources are not needed, go to No. 6		
5.	Contact qualified personnel or resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #5.a.		
6.	Start malfunction diagnosis.		
7.	Determine if other resources are needed to fix the malfunction (qualified technician, electrician, contractor, on-site resources, manufacturer's representative, or other). If other resources are not needed, go to No. 9		
8.	Contact other qualified resource: a. Record contact name, date and time: b. Contact site representative with information recorded in #8.a.		
9.	Fix the malfunction.		
	Once the malfunction is fixed, re-start the system per SOP if it had been shut down, and record start-up times and dates on this form.		
	Record date that malfunction occurred, date that malfunction was repaired, and total time that system was out of service in boxes in Section 1 of this form.		
12.	Sign this form, copy it, and place it in the Start-up, Shutdown, Malfunction Report Form file.		
13.	If the procedures listed above were not followed, contact the site engineer immediately.		

Signature 2 2 De 7 2 / 2

 $^{^{\}star\star} \text{If SOP}$ in SSM Plan was not followed, notify site engineer immediately.